


## AirSafe AS1

### Technical Data Sheet



<b>General properties</b>	
<b>Outside Dimension</b>	400 x 555 x 445 mm
<b>Chamber Dimension</b>	320 x 460 x 325 mm
<b>Spool Configuration</b> (How many Spools you can fit inside the AirSafe AS1)	Setup 1 – 4 x 1 kg Setup 2 – 2 x 2,5 kg Setup 3 – 1 x 5kg * Combinations of Setup 1 and Setup 2 possible
<b>Maximum Total Spool Weight</b>	5 kg
<b>Maximum Spool Diameter</b>	330 mm
<b>Filament Feedthrough</b>	On the backside for max. 4 filaments. * PTFE tube with outside diameter of 5-6 mm necessary. * PTFE tube not included.
<b>Compatible Materials</b>	No Restrictions
<b>Adjustable Drying Setting</b>	Continuos
<b>Minimum relative Humidity</b>	< 20% r.H.
<b>Weight of AirSafe AS1 (w/o Spools)</b>	11,4 kg
<b>Technical Properties</b>	
<b>Maximum Power Consumption</b> (The peak power consumption of the AirSafe AS1)	100 W
<b>Average Power Consumption</b>	12 W
<b>Connection Type</b>	230V/50Hz EU-Plug
<b>Drying Technique</b>	Self Regenerating Molecular Filter
<b>Maintenance &amp; Safety</b>	
<b>Maintenance Interval</b>	No Maintenance Needed
<b>CE – Conformity</b>	EU
<b>Spool-Chamber Door Lockable</b>	Yes
<b>Service and Support</b>	
<b>Guarantee</b>	6 months