

## Xioneer VXL GO

### Technical Data Sheet



<b>General properties</b>	
<b>Container Dimension</b>	380 x 240 x 210 mm
<b>Tank Volume</b>	10 Liter
<b>Weight</b>	w/o fluid: 2 kg with fluid: approx. 12 kg
<b>Adjustable Temperature Range</b>	25 °C – 60 °C
<b>Temperature Adjustment</b>	Continuous
<b>Heating Time (10L, 20°C – 60 °C)</b>	25 minutes
<b>Recommended Model Materials</b>	No restrictions
<b>Recommended Support Materials</b>	<b>Xioneer VXL 70, Xioneer VXL 90</b>
<b>Recommended Detergents</b>	<b>Xioneer VXL EX, Xioneer VXL solve</b>
<b>Technical Properties</b>	
<b>Maximum Power Consumption</b> (The peak power consumption of the rod)	850 W
<b>Connection Type</b>	230V/50Hz EU-Plug
<b>Dissolving Technique</b>	Heat, Agitation, Dissolving Agent
<b>Maintenance &amp; Safety</b>	
<b>Maintenance Interval</b>	After draining solution, on demand
<b>CE – Conformity</b>	EU
<b>Service and Support</b>	
<b>Guarantee</b>	6 months